

AKUSTUS DESIGNS INFO@AKUSTUS.COM AKUSTUS.COM

# **Stripes Ceiling Tiles**




**STRIPES** 





Stripes Ceiling Tiles showcase the timeless appeal of simple patterns formed by parallel lines. Where most ceiling tiles are made with only acoustic benefits in mind, these tiles are fashioned to provide aesthetic appeal as well. Flat and flush with the ceiling or protruding from the ceiling in the shape of a box, these tiles can be placed in a ceiling grid system to transform an office in the middle of downtown or a store in the middle of a shopping mall.


# **How to Specify**

Step by step instructions on how to specify <u>Stripes</u> <u>Ceiling Tiles</u>.









01

Choose edge variation. (pg 03)

02

Choose panel size. (pg 04)

03

**STRIPES** 

Option A

Choose panel design and create your own configuration.

**Option B** 

Choose one of our configurations. (pg 05-06)


04


Choose colour. (pg 07)

03 **STRIPES CEILING TILES AKUSTUS.COM** 


# **Edge Variations**


Choose from 3 different edges. No matter the variation, the panel will easily lay in to a standard T-grid system.







# **Tegular Edge**





# **Box Edge**





# Standard Thicknesses (mm)

**Square** 12, 18, 24

**Tegular** 18, 24

50, 75, 100, 150 Box

**CEILING TILES** 

# **Dimensions**


# Standard Dimensions (mm)

605 W x 605 L 605 W x 1215 L

# Customization


Width and Length can be customized to fit your space.

# Square



<sup>\*</sup> Square Edge option, Stripes A design shown here

# Rectangle




# **Panel Designs**


Stripes come in 3 standard design variations.

# Customization

Custom pattern, shape, and size available.

# Design A






06 STRIPES CEILING TILES AKUSTUS.COM


# Configurations

Examples of how the panels can be arranged.


Config 1



Config 2



Config 3



# **Standard Colours**

Choose from any one of our standard colours.

Don't see something you love? Ask us about creating your own custom colour.

All colours available in 9, 12, 18, and 24 mm unless noted otherwise.

\* 12 mm / 24 mm only



80

AKUSTUS.COM

# **Product Specifications**

# **Stripes Ceiling Tiles**

# Composition

100% polyester fibre

## **VOC Emissions**

CDPH (CA 01350)

# **Antimicrobial Testing**

Mould & mildew resistant

# **Fire Rating**

- ASTM E84 Class A
- CAN/ULC-S102.2-10



**AKUSTUS** 

# Sustainability


- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles

## **Colour & Texture Variations**

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

# **Sound Absorption Graph**

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
12 mm	0.97	1.00	0.96	0.85	0.71	0.82	0.90	0.91	0.96	1.00	0.99	0.99	0.90	0.92
24 mm	0.87	0.87	0.87	0.84	0.78	0.91	0.98	1.02	1.04	1.04	1.07	1.08	0.95	0.95

# **Product Care**

# **Handling & Storage**

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements.

# Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

# Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt.
Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products.

