Modelo Lines Panels



INFO@AKUSTUS.COM




MODELO LINES


Modelo Lines features a myriad of patterns cut as grooves onto the surface of a panel. Ranging from the intricate linework of Glint to the organic furrows of Bark, this series of panels showcases how thin lines can add texture and ambience while reducing noise and distraction. Mount it to the wall or hang it from the ceiling and discover how different your space can feel.

How to Specify

Step by step instructions on how to specify <u>Modelo</u> <u>Lines Panels</u>.

1





01

02


Choose thickness. (pg 03)

02

Choose panel design and create your own configuration. (pg 04-05) 03


Choose colour. (pg 06)





04


Choose installation method. (pg 07-09) 03



* Deck design shown here

to fit your space.

A K U S T U S




PANELS

AKUSTUS.COM

Panel Designs

04

Play with the following designs for Modelo Lines Panels.



Customization

Custom pattern, shape, and size available. Patterns may be reflected. By default, designs are on one side only for screens and for wall panels. Designs are available on both sides for screens.

0


0




Loom (B)




Savannah (B)








Savannah (C)



Origami




Savannah (D)


Configurations

Examples of how the panels can be arranged.


Config Savannah





Config Ravine



Config Savannah







"R" indicates a reflected design.

Note

PANELS

MODELO LINES

Standard Colours

Choose from any one of our standard colours.

Pure White **Urban Grey** Warm Grey **Cool Grey** Pumice SP 07 SP 79 SP 11 SP 76 SP 36 Beige Taupe Grey* Sandstone Castlerock* lvory SP 77 SP 90 SP 04 SP 12 SP 80 **Blush Pink** Red Mustard* Orange Yam SP 81 SP 08 SP 46 SP 28 SP 87 Lagoon* Sky Blue Pale Teal Dark Turquoise Azure* SP 74 SP 84 SP 71 SP 85 SP 25 Olive* Moss* **Desert Sage** Peacock* **Ocean Green*** SP 88 SP 89 SP 78 SP 82 SP 86

Don't see something you love? Ask us about creating your own custom colour.

All colours available in 9, 12, 18, and 24 mm unless noted otherwise.

* 12 mm / 24 mm only

ΛΚUSTUS

06

PANELS

AKUSTUS.COM



Mid Grey SP 37



Krypton SP 30



SP 05



Navy SP 01



Forest Green SP 17



Graphite SP 03



Purple SP 50



Chartreuse SP 43



Deep Sea Blue* SP 83



Black SP 13



Plum SP 72



Aquamarine SP 73




Midnight Blue SP 19


Wall Installation


This is an overview of the available installation methods. Check out our installation guide for more details.

Construction Adhesive


Push Mount Clips







Concealed Mechanical Fasteners





Screen Installation Option 01

08


Aircraft Wire Suspension Kit

Each screen is suspended by its own set of aircraft wires.






Screen Ceiling Mount (Default)




T-bar Clips (Alternative)



Panel Clamps For 18, 24 mm thickness

Aluminum Trim For 12 mm thickness



Screen Installation Option 02


Sliding Track Suspension Kit

Screens are suspended from tracks mounted to the ceiling.

Installation Surface Tracks must be mounted to a flat, stable, and sturdy surface




Top-Down View
Tracks can be installed in multiple rows to layer the screens



Sound Absorption Graph

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
Wall Panel 12 mm	0.04	0.09	0.13	0.15	0.28	0.38	0.48	0.54	0.58	0.66	0.73	0.65	0.40	0.39
Wall Panel 18 mm	0.10	0.12	0.18	0.30	0.44	0.63	0.72	0.81	0.87	0.91	0.94	0.97	0.60	0.58
Wall Panel 24 mm	0.14	0.24	0.29	0.41	0.69	0.80	0.87	0.94	0.96	0.94	0.88	0.86	0.70	0.67
Screen 12 mm	0.43	0.48	0.59	0.71	0.85	0.92	0.93	0.96	0.94	0.94	0.93	0.93	0.80	0.80
Screen 18 mm	0.28	0.34	0.48	0.64	0.79	0.96	1.03	1.05	0.99	0.98	0.94	0.92	0.80	0.78
Screen 24 mm	0.58	0.68	0.85	0.94	1.00	1.00	1.06	1.04	1.05	1.02	1.04	1.04	0.95	0.94

Product Specifications

Modelo Lines Panels

Composition

100% polyester fibre

VOC Emissions

CDPH (CA 01350)

Antimicrobial Testing

Mould & mildew resistant

Fire Rating

- ASTM E84 Class A
- CAN/ULC-S102.2-10

Declare.

Sustainability

- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles

Colour & Texture Variations

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

٨	v		~	-		~
Λ	N	υ	Э		υ	2

PANELS

AKUSTUS.COM

Wall Panel 12 mm

Wall Panel 18 mm

Wall Panel 24 mm

Screen 12 mm

Screen 18 mm

Screen 24 mm



Frequency [Hz]

Product Care

Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements. Maintenance

products.

Lightly brush or gently vacuum to

remove dust from polyester felt.

Clean with warm water and mild,

non-toxic soap to remove spills. Test solution on an inconspicuous spot

before applying to more visible areas.

Blot with a dry cloth after applying

the solution to avoid saturating

the material. Avoid applying too much pressure when cleaning the

Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

A K U S T U S

MODELO LINES

