

AKUSTUS DESIGNS WALL PANELS INFO@AKUSTUS.COM AKUSTUS.COM

# **Impressio Wall Panels**



**IMPRESSIO** 





The Impressio Wall Panel combines the acoustic benefits of polyester felt with the creative possibilities of digital printing.


AKUSTUS' proprietary Felt Print technique produces prints with vivid colours on polyester felt without clogging up the pores that give the panels their sound-absorbing effect. Print a logo, a piece of artwork, a photo or a texture on to the panel and mount it to the wall. In a conference room or in the waiting room, these wall panels will complement the look and sounds of whatever space you place them in.


# **How to Specify**

Step by step instructions on how to specify <a href="Impressio Wall Panels">Impressio Wall Panels</a>.









01

Choose edge option and thickness.

(pg 03)

02

Specify panel size. (pg 04)

03

Specify print colour or design. (pg 05-06)

04

Choose installation method. (pg 07)

# **Edge Options**

Choose between a thicker, printed edge or a flatter, square edge.

## **Box Edge**

Edges are folded and printed, creating a premium look and feel.

#### **Square Edge**

Edges are unprinted and substrate colour is visible.

#### Standard Thicknesses (mm)

Box

25, 38, 50

**Square** 12, 18, 24

## **Box Edge - Gallery Wrap**

Print continues along the edges of the panel.



## **Box Edge - Museum Wrap**

Black ink is printed along the edges for a uniform border.



## **Square Edge**

Print is only on the face of the panel.



04 **IMPRESSIO** WALL PANELS AKUSTUS.COM

# **Dimensions**

# Standard Dimensions (mm)

1100 W x 2650 H (max.) Box

1220 W x 2745 H (max.)

## Customization

Width and Height can be customized to fit your space.

# **Box Edge** 2650 mm (104.3 in)

1100 mm (43.3 in)

# **Square Edge**



1220 mm (48 in)

# Colourways

The sky's the limit when it comes to custom printed colours, that's why we've curated some to get your creative juices flowing. Cover the entire panel with a single colour or mix and match to use them in a custom graphic.

We'll match custom colours ranging from paint chips to corporate colours.







Madrid



Sao Paulo





# **Textures**

Create a natural look and feel with printed textures.



White Oak

















Have something you want to print? Talk to us about printing a custom texture, design or image.

Cafe Oak Golden Oak Teak


Walnut

07 IMPRESSIO WALL PANELS AKUSTUS.COM


# Installation

This is an overview of the available installation methods. Check out our installation guide for more details.


## **Construction Adhesive**



# **Push Mount Clips**



**Z-Clips** 



80

IMPRESSIO WALL PANELS AKUSTUS.COM

# **Product Specifications**

## **Impressio Wall Panels**

#### Composition

100% polyester fibre

#### **VOC Emissions**

CDPH (CA 01350)

#### **Antimicrobial Testing**

Mould & mildew resistant

#### **Fire Rating**

- ASTM E84 Class A
- CAN/ULC-S102.2-10



#### Sustainability


- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles

#### **Colour & Texture Variations**

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

# **Sound Absorption Graph**

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
Square 12 mm	0.04	0.09	0.13	0.15	0.28	0.38	0.48	0.54	0.58	0.66	0.73	0.65	0.40	0.39
Square 18 mm	0.10	0.12	0.18	0.30	0.44	0.63	0.72	0.81	0.87	0.91	0.94	0.97	0.60	0.58
Square 24 mm	0.14	0.24	0.29	0.41	0.69	0.80	0.87	0.94	0.96	0.94	0.88	0.86	0.70	0.67
Box 38 mm	0.23	0.30	0.46	0.56	0.76	0.91	1.06	1.15	1.17	1.20	1.22	1.17	0.85	0.85
Box 50 mm	0.35	0.45	0.68	0.79	0.99	1.13	1.20	1.22	1.26	1.23	1.22	1.17	0.95	0.97



# **Product Care**

## **Handling & Storage**

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements.

#### Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

#### Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt. Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products.

