

Batten 3D Panels






The Batten 3D Panel exemplifies how practical elements of construction and architecture can be featured as decorations in their own right. Mount Batten to the wall to absorb and reduce noise in a pub or in the waiting area of a clinic.


How to Specify

Step by step instructions on how to specify Batten 3D Panels.




01

Choose panel design.
(pg 03-04)



02

Choose colour.
(pg 05)




03

Choose installation method.
(pg 06)

Dimensions

Narrow


1206 mm (47.5 in)



2745 mm (108.1 in)

Wide

1200 mm (47.2 in)



2745 mm (108.1 in)

Standard Dimensions (mm)

Narrow 1206 W x 2745 H


Wide 1200 W x 2745 H

Standard Thicknesses (mm)

Narrow 36

Wide 82

Edge Detail




Customization

Width and Height can be customized to fit your space.



Panel Designs

Batten comes in 2 standard designs which feature different slat dimensions.

Narrow



Wide



Customization

Custom slat width and depth available.

Standard Colours


Choose from any one of our standard colours.



Pure White
SP 07




Urban Grey
SP 79




Pumice
SP 11




Warm Grey
SP 76




Cool Grey
SP 36



Mid Grey
SP 37



Graphite
SP 03



Black
SP 13




Ivory
SP 77




Beige
SP 04




Sandstone
SP 12



Taupe Grey*
SP 90




Castlerock*
SP 80




Krypton
SP 30




Purple
SP 50




Plum
SP 72




Blush Pink
SP 81




Red
SP 08




Orange
SP 46




Yam
SP 28




Mustard*
SP 87




Sunflower
SP 05




Chartreuse
SP 43




Aquamarine
SP 73




Pale Teal
SP 74




Lagoon*
SP 84



Dark Turquoise
SP 71



Azure*
SP 85



Sky Blue
SP 25




Navy
SP 01




Deep Sea Blue*
SP 83




Midnight Blue
SP 19




Olive*
SP 88




Moss*
SP 89



Desert Sage
SP 78



Peacock*
SP 82



Ocean Green*
SP 86



Forest Green
SP 17

Don't see something you love? Ask us about creating your own custom colour.


All colours available in 9, 12, 18, and 24 mm unless noted otherwise.

* 12 mm / 24 mm only


Installation

This is an overview of the available installation methods. Check out our installation guide for more details.


Construction Adhesive




Push Mount Clips



Z-Clips



Concealed Mechanical Fasteners



Product Specifications

Batten 3D Panels

Composition

100% polyester fibre

VOC Emissions

CDPH (CA 01350)

Antimicrobial Testing

Mould & mildew resistant

Fire Rating

- ASTM E84 Class A
- CAN/ULC-S102.2-10

Declare.

Sustainability


- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles

Colour & Texture Variations

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

Sound Absorption Graph

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
0.17	0.23	0.34	0.50	0.63	0.77	0.86	0.92	1.03	1.00	0.99	0.98	0.70	0.70

Product Care

Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements.

Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

