
Carton Baffles



INFO@AKUSTUS.COM



CARTON


Whatever their orientation or arrangement, Carton Baffle's lines lead to more peaceful soundscapes and more stunning environments. The system's aluminum frame comes equipped with baffle hooks so that installing the baffles is as easy as just pushing them onto the frame. With Carton Baffles covering the ceiling, you can elevate the atmosphere of any room.


CARTON

How to Specify

Step by step instructions on how to specify Carton Baffles.







03

(pg 04)


01 Choose baffle dimensions. (pg 03)

02 Choose baffle spacing. (pg 04)

04 Choose configuration or Choose colour or create your own. texture. (pg 05-06)



02




05


Choose installation method. (pg 07)

Dimensions


Carton Baffle comes in 3 standard sizes.




Length and Height can be customized to fit your space.



CARTON




103 mm (4.1 in)




Configurations

Vary baffle sizes and spacing to create a dynamic look.

04









Config 1





Config 2





Standard Spacing Options


25 mm

50 mm

Spacing measured from edge to edge. Custom spacing available.

Config 3





CARTON

Standard Colours

Choose from any one of our standard colours.



Don't see something you love? Ask us about creating your own custom colour.

All colours available in 9, 12, 18, and 24 mm unless noted otherwise.

* 12 mm / 24 mm only

05

A K U S T U S

BAFFLES

AKUSTUS.COM



Mid Grey SP 37



Krypton SP 30



SP 05



Navy SP 01



Forest Green SP 17



Graphite SP 03



Purple SP 50



Chartreuse SP 43



Deep Sea Blue* SP 83



Black SP 13



Plum SP 72



Aquamarine SP 73



Midnight Blue SP 19

Textures

Create a natural look and feel with printed textures.




CARTON

Have something you want to print? Talk to us about printing a custom texture, design or image.

Cafe Oak

Golden Oak





Teak


06

A K U S T U S


Walnut

Installation

Baffle Hook Suspension Kit



- Caps match material colour
- Connect adjacent baffles



Product Specifications

Carton Baffles

Composition

100% polyester fibre

VOC Emissions

CDPH (CA 01350)

Antimicrobial Testing

Mould & mildew resistant

Fire Rating

- ASTM E84 Class A
- CAN/ULC-S102.2-10

Declare.

Sustainability

- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles


Colour & Texture Variations

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

CARTON

Sound Absorption Graph

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
Spacing 25 mm	0.12	0.15	0.31	0.32	0.48	0.60	0.78	0.91	1.06	1.14	1.24	1.30	0.70	0.70
Spacing 50 mm	0.07	0.09	0.17	0.21	0.33	0.43	0.58	0.70	0.83	0.92	1.02	1.12	0.55	0.54

BAFFLES

AKUSTUS.COM

Product Care

09

Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements.

Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

ΛΚUSTUS

Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt. Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products. CARTON

AKUSTUS.COM



