
AKUSTUS DESIGNS WALL PANELS INFO@AKUSTUS.COM AKUSTUS.COM

# **Square Wall Panels**



**SQUARE** 





Square Wall Panels are the pixels of wall coverings: the basic unit by which wonderful wall compositions are created. In an auditorium or in a gymnasium, mount these panels to absorb unnecessary reverb and augment the visual appeal of the room.


02 SQUARE


# **How to Specify**

Step by step instructions on how to specify <u>Square</u> <u>Wall Panels</u>.









AKUSTUS.COM

WALL PANELS

O1
Choose thickness. (pg 03)

O2
Choose panel size. (pg 03)

O3 Choose colour. (pg 04) O4
Choose installation method.
(pg 05)

WALL PANELS

# **Dimensions**

### Standard Dimensions (mm)

300 W x 300 H 600 W x 600 H

### Standard Thicknesses (mm)

12, 18, 24

### **Edge Detail**



Bevel Edge




Square Edge (Optional)


### Customization

Width and Height can be customized to fit your space.

### Small



### Large



# **Standard Colours**

Choose from any one of our standard colours.

Don't see something you love? Ask us about creating your own custom colour.

All colours available in 9, 12, 18, and 24 mm unless noted otherwise.


\* 12 mm / 24 mm only




# Installation

This is an overview of the available installation methods. Check out our installation guide for more details.


### **Construction Adhesive**




### **Push Mount Clips**



### **Z-Clips**



### **Concealed Mechanical Fasteners**



06

# **Product Specifications**

### **Square Wall Panels**

#### Composition

100% polyester fibre

#### **VOC Emissions**

CDPH (CA 01350)

#### **Antimicrobial Testing**

Mould & mildew resistant

#### **Fire Rating**

- ASTM E84 Class A
- CAN/ULC-S102.2-10



**AKUSTUS** 

### Sustainability

- 100% recyclable
- LBC Red List free
- Contributes to LEED certification
- Free of toxic substances and of off-gassing
- Made with ~60% recycled content from plastic water bottles


#### **Colour & Texture Variations**

The felting and dyeing process that forms the material contributes to its unique texture but also to variations in texture and colour from panel to panel. Products will be provided within an acceptable range of variation.

SQUARE WALL PANELS AKUSTUS.COM

# **Sound Absorption Graph**

The following values reflect the acoustic properties of the product as tested in accordance with ASTM C423-09a.



	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	NRC	SAA
12 mm	0.04	0.09	0.13	0.15	0.28	0.38	0.48	0.54	0.58	0.66	0.73	0.65	0.40	0.39
18 mm	0.10	0.12	0.18	0.30	0.44	0.63	0.72	0.81	0.87	0.91	0.94	0.97	0.60	0.58
24 mm	0.14	0.24	0.29	0.41	0.69	0.80	0.87	0.94	0.96	0.94	0.88	0.86	0.70	0.67

### **Product Care**

### Handling & Storage

Handle products with care so as to avoid folding the polyester felt, chipping its edges, or indenting its faces. Store products in their original containers in a well-ventilated area until the intended application environment is ready for installation. Allow products to acclimatize to environmental conditions. Lay them flat on their faces; do not stand them on their edges. Protect from moisture, heat, direct sunlight, and the elements.

#### Warranty

AKUSTUS warrants the construction and finish of all our products to be free from defects in material and workmanship for a period of 1 year from the date of purchase.

#### Maintenance

Lightly brush or gently vacuum to remove dust from polyester felt. Clean with warm water and mild, non-toxic soap to remove spills. Test solution on an inconspicuous spot before applying to more visible areas. Blot with a dry cloth after applying the solution to avoid saturating the material. Avoid applying too much pressure when cleaning the products.

